

# HN-Useries

# 電木射出機

Thermosetting Injection Molding Machine

# 優異特點 Specific Features



#### ● 新式調模機構

調模機構與調模壁採整體式設計,使四支大柱 受力均匀,鎖模力調整簡易準確。

#### New Mold Adjusting Mechanism

The new mold adjusting platen mechanism design doesn't require its mounted nut for torque tuning and distributes force evenly on the tie bars.



### ● 無給油軸承

曲肘及車壁活動部位均採用無給油軸承,減少 潤滑油使用,降低保養成本並可減少油污,提 升機台清潔度。

#### Oil-less Bearing

Oil-less bearing on the moving parts of platen and toggle, greatly reduces maintenance cost, and provides for a cleaner production environment.







#### • 自動潤滑系統

循環式電動注油系統,油量分配平均,潤滑效率 高,增長曲肘壽命。

#### Automatic Lubrication System

An automatic lubrication system circulates and distributes oil equally for greater efficiency in lubrication and enhanced toggle life.



#### 全新網路型微電腦控制器

全新網路型控制器,可搭配半閉及全閉路油壓系統,並 具備人性化圖形操作界面、線上曲線監測功能及中央網 路連線管理。

#### All-new Control System

The new control system is capable of producing under semi-closed and closed-loop systems, a personalized graphic operation interface, and production data management via centralized web link.



#### 新式專利射移結構

新型導柱式結構,跨距縮短,避免料管前傾及 導柱下垂變形。使用二硫化鉬塗佈襯套,阻力 小,移動快速,且永久免潤滑,潔淨度高。

### New Patented Injection Sliding Structure

The new pillar guiding plate structure is shortened to avoid barrel inclination and deformation. And with Molybdenum Disulfide coated bushings, it produces a less resistant, faster moving, very clean, oil-free injection sliding structure.



#### ● 高剛性機架結構

精簡堅固之設計,經有限元素分析變形量及應力分 佈,確保機架結構及強度達到最佳化,使HN系列 機種「穩如泰山」。

#### Highly Rigid Structure Frame

Designed based on Finite Element Analysis (FEA) for Stress and Strain effects to ensure the HN's excellent frame structure.

#### 高效節能的伺服動力系統

配置交流永磁同步高性能的伺服電機,實現系 統壓力和流量閉環控制,可節能約30-70%。

### High Efficiency Servo Power System

Adopting AC / PM synchronous servo motor to achieve system pressure and close loop controlling, and save power about 30-70%.

# 標準及選購配備 Standard & Optional Accessories

配備項目	ITEM	HN- 125U	HN- 150U	HN- 200U	HN- 250U	HN- 300U	HN- 350U	HN- 470U	HN- 530U
C級雙合金螺桿	C-Bi-alloy Screw	•	•	•	•	•	•	•	•
開關模比例閥控制	Proportional valve for mould open and close	0	0	0	0	0	0	0	0
多段數位背壓(螢幕設定)	Multi-stage back pressure control (Screen set up)	0	0	0	0	0	0	0	0
多段數位背壓(螢幕設定及顯示)	Multi-stage back pressure control (Screen set up and display)	0	0	0	0	0	0	0	0
射出電阻尺	L/P for injection unit	•	•	•	•	•	•	•	•
模壁T型槽	T-slot platen	_	R <del></del>	848	•	•	•	•	•
模壁T型墊板	T-slot board	0	0	0		-	-	(°-)	
隔熱墊板	Insulator sheets	•	•	•	•	•	•	•	•
模定位圏	Check ring of mold	•	•	•	•	•	•	•	•
曲肘電動注油器	Auto lubrication system for toggle	•	•	•	•	•	•	•	•
車壁潤滑:電動注油器	Auto lubrication system (platen)	•	•	•	•	•	•	•	•
雙中子	Double core pull device	0	0	0	0	0	0	0	•
單中子(一公)	Single core pull device	•	•	•	•	•	•	•	-
計時(次)轉牙	Unscrew device by counter or timer	0	0	0	0	0	0	0	0
夾模電阻尺	L/P for clamping unit	•	•	•	•	•	•	•	•
頂出電阻尺	L/P for ejection unit	•	•	•	•	•	•	•	•
單風托(一公一母)	Air ejector sets	0	0	0	0	0	0	•	•
機架架高(落下口取物)	High base	_	-	-	-	_	_	-	-
成品落下口	Article Collecting Channel	•	•	•	•	•	•	•	-
電動安全門	Automatic safety gate (Electric type)	-	_	-	_	_	-	-	•
水流分佈器4入4出(銅製)	Water manifold-4 in & 4 out (copper)	•	•	•	•	•	-	1-1	-
水流分佈器10入10出(銅製)	Water manifold-10 in & 10 out (copper)	0	0	0	0	0	0	0	•
自封式磁性吸油過濾器	With check valve magnetic suction filter	_	-	-	-	-	-	•	•
雙迴路(開模與托模同動)	Double loops system (mould open-ejector start)	0	0	0	0	0	0	0	0
油溫顯示	Oil temperature display for hydraulic system	•	•	•	•	•	•	•	•
伺服節能系統	Servo power-saving system	•	•	•	•	•	•	•	•
電眼檢出	Photo cell drop-out checking device	0	0	0	0	0	0	0	_
FCS-6510S微電腦控制器(彩色)	FCS-6510S controller (color screen)	•	•	•	•	•	•	•	•
資料保護鎖(硬體鎖)	Data look function (key)	•	•	•	•	•	•	•	•
電控穩壓器	Power stabilizer	0	0	0	0	0	0	0	0
三色警示燈	Three colors alam light	•	•	•	•	•	•	•	•
CE安全插座	CE safty sockt	•	•	•	•	•	•	•	•
電源插座	Power socket (110V/220V)	0	0	0	0	0	0	0	0
主電源斷路器	Main power breaker	•	•	•	•	•	•	•	•
油壓、電氣雙重保護裝置	Dual safty device : hydraulic and electrical	•	•	•	•	•	•	•	•
不鏽鋼漏斗	Stainless hopper	_	_	_	<b>A</b>	_	_	•	
乾燥機	Hopper dryer	0	0	0	0	0	0	0	0
抽料機	Auto loader	0	0	0	0	0	0	0	0
模温機	Mold temperature controller	0	0	0	0	0	0	0	0
乾燥機磁鐵	Magnet for hopper dryer	0	0	0	0	0	0	0	0
吊桿組	Mold lifting hanger set	0	0	0	-	-		V-8	_
避震器	Anti-vibration mounting pad	•	•	•	•	•	•	•	•
填料台	Filling material stand	-	-	27-3	-	-	_	-	-
工具箱組	Tool box set	•	•	•	•	•	•	•	•
電器及其他附件	Accessory for electrical and others	•	•	•	•	•	•	•	•

<sup>●</sup> 標準配備 Standard

<sup>○</sup>選購配備 Option

<sup>▲</sup> 選附配備 Free Option



## 富強鑫集團 FCS Group

#### 富強鑫精密工業股份有限公司

Fu Chun Shin Machinery Manufacture Co., Ltd.

71841臺灣台南市關廟區埤頭里保東路269號

No.269, Baodong Road, Pitou Village, Guanmiao District, Tainan City 71841, Taiwan TEL: +886-6-5950688 • FAX: +886-6-5951129 • E-mail: fcsco@fcs.com.tw

東莞富強鑫塑膠機械製造有限公司 Dongguan Fu Chun Shin Plastic Machinery Manufacture Co., Ltd.

中國廣東省東莞市大朗鎮石廈管理區金廈東路18號 郵編:523792 No.18, Jinsha East Road, Shixia Administration District, Dalang Town, Dongguan City 523792, Guangdong Province, China TEL: +86-769-83313753 • FAX: +86-769-83181903 • E-mail: cdg@fcs.com.tw

富強鑫(寧波)機器製造有限公司 Fu Chun Shin (Ningbo) Machinery Manufacture Co., Ltd.

中國浙江省寧波市江北區海川路115號 郵編:315032 No.115, Haichuan Road, Jiangbei District, Ningbo City 315032, Zhejiang Province, China TEL: +86-574-56138688 • FAX: +86-574-56138600 • E-mail: cnb@fcs.com.tw

#### 印度富強鑫

#### FCS Manufacturing (India) Private Limited

Block Number 218, Xcelon Industrial Estate, Near Intas Pharmaceutical, Village Chancharvadi Vasna, Sarkhej Bavla Road, Taluka Sanand, Ahmedabad, Gujarat - 382213 TEL: +91-99-98897768 \* E-mail: fcsco@fcs.com.tw

